

MIX 200

Planetary mixer with forced action for premixed in bags and traditional mortars

Standard Equipment

- ✓ Single-phase 2.5 kW 2P 230V / 50Hz electric motor or Honda petrol engine GXV160 3.2 kW (2 kW cont.)
- ✓ Magnetothermic switch with IP55 minimum voltage coil and IP67 plug (electric version)
- ✓ I-DUST grate with connector tube for vacuum cleaner and bag breaker blade
- ✓ Electric safety grate opening
- ✓ Mixing paddles adjustable in height up to 18 mm
- ✓ Lifting hooks positioned on 4 sides and forklift guides
- ✓ Loading / unloading adjustable height in 3 positions 550/680/810 mm
- ✓ Oscillating discharge outlet to avoid clogging and facilitate cleaning
- ✓ Bonnet and hood fastening with silent and easy-to-use Valpa elastic closures
- ✓ Pneumatic wheels and axle with independent elastic suspension for excellent mobility on the building site
- ✓ Version approved for road towing (with optional light bar kit added)

Optional Accessories

- ✓ Light bar kit (required for road towing)
- ✓ Rubber paddles kit
- ✓ Outlet slide kit for loading on Step 120

Applications

Large capacity and excellent maneuverability thanks to the small size and road tires. The I-DUST grate (standard) limits the spread of dust in the surrounding environment while loading. Easy adjustment of the belt pull. Tested and reliable gearbox of MIX 120 Plus origin. The height of the legs adjustable in 3 positions allows to easily load and unload the material.

Suitable for mixing:

- Premixed or traditional cementitious screed, also with addition of fibers and / or additives
- Pre-dosed or traditional lightened screed, with expanded clay with grain size > 20 mm
- Colored rubber granulate for anti-trauma flooring
- Self-levelling anhydride / cement based screeds
- Thermal insulating cork or polystyrene based screeds
- Cement / lime / gypsum based plasters
- Fiber-reinforced structural plasters also with the addition of additives
- Restorative plasters
- Traditional plasters
- Binders / mortars for injections
- Polystyrene or cork based insulating plasters
- Fiber-reinforced mortars for reinforcement
- Premixed / traditional masonry mortars
- Filling concrete with 6 mm grain size
- Concrete for continuous draining flooring
- Mortars for heat protection
- Fireproofing



MIX 200

Drum capacity	l	200
Mixing performance	l	140
Drum diameter	mm	800
Paddle speed - electric / petrol	rpm	32 / 31
Motor power - electric / petrol	kW	2.5 / 3.2
Electric power supply	V / Hz	230 / 50 Sph 115 / 60 Sph
Motor power: electric motor / petrol engine	kW	2.5 (1.1) / 3.2
Running current 230 V (115 V)	A	15.9 (14.5)
SPL in operator's position - electric / petrol	dB(A)	70 / 88
Discharge height: max. - min.	mm	810-550
Machine weight: electric motor/petrol engine	kg	260/265
Dimensions with drawbar w/l/h	mm	1080/2525/1160
Dimensions for transport w/l/h	mm	1080/1410/1320
Max stackability*		2 (h 2280 mm)

(*) Number of stackable pieces and total height including pallet